



PCICASE Europe B.V.
Nikkelstraat 28
4823 AB BREDA
The Netherlands
Tel. +31-76-5423433
Fax. +31-76-5423420
www.pcicase.nl
info@pcicase.nl



CRS-C8045-08 Specification sheet.

Features:

- Dimensions (WxHxD): 150 x 86 x 140mm
- 450W max. output
- 80PLUS certified
- 80mm fan
- ATX12V 2.2 compliant
- Silent Fan Speed Control
- Build in DC remote ON/OFF , PG/PF TTL signal
- Operating temperature range from 0°C to 50°C
- Harmonic : IEC-1000-3-2 CLASS D
- Meet FCC : Class B
- Meet CISPR22 : Class B
- Meet BSMI : Class B
- Meet CUL(UL60950)
- Meet TUV(EN60950)
- Meet CB(IEC950)
- Meet CE
- Meet CCC
- MTBF: 100Khrs minimum at 25°C

Specifications:

Input voltage: 100~240V AC
Input frequency: 47~63Hz
Input current: 6.0A max. @ 115V AC / 3A max. @ 230V AC
Leakage current: 3.5mA max.
Efficiency: over 80% efficiency on 20%, 50% and 80% loads

Output specifications:

Total output power: 450W max.

Output	Min. load	Max. load	Regulation	Ripple&noise
+5V	0.5A	15.0A	+/-5%	50mV
+3.3V	0.3A	24.0A	+/-5%	50mV
+12V1	0.3A	17.0A	+/-5%	120mV
+12V2	0.5A	16.0A	+/-5%	120mV
-12V	0.0A	0.3A	+/-10%	120mV
+5Vsb	0.0A	3.0A	+/-5%	50mV

a professional case manufacturer



PCICASE Europe B.V.
Nikkelstraat 28
4823 AB BREDA
The Netherlands
Tel. +31-76-5423433
Fax. +31-76-5423420
www.pcicase.nl
info@pcicase.nl



CRS-C8045-08

Cabling overview

